

Low PIM Directional Coupler

Model No.: DC08-0727DF60

- Excellent passive intermodulation (PIM), -160dBc guaranteed.
- Wideband frequency range: AWS 700, CDMA 800/1900, GSM 900/1800 UMTS, LTE and WiMAX.
- 200 watts average high power rating
- Minimal RF insertion loss
- IP65 for both indoor and outdoor operations



Product Specifications:

Electrical		Mechanical	
Frequency Range (MHz)	698-2700	Connectors	7-16 DIN-Female
VSWR	1.2	Connector Finish	Tri-metal
Return Loss	20.8dB	Connector Inner Conduct	Silver Plating
Coupling Loss	8.0 dB	Housing Finish	Painting
Coupling Tolerance	±1.0 dB	Width	74.9 mm
Insertion Loss	1.1 dB	Length	168.5mm
Dissipative Loss	0.2 dB	Height	26.0 mm
Power Rating	200 W	Weight	560.0 g
Maximum Reflected Power	60 W	Environmental	
Maximum Peak Power	1 kW	Temperature Range	-40 °c to 75 °c
Passive Intermodulation(PIM), 3 rd order@2*43dBm	-160dBc	Relative Humidity	0 to 100%
Input Impedance	50 Ω	Applications	Indoor & Outdoor
		IP Level	IP65

Engineering Drawings

